



The Vertical World

Technical specification



1

1- **The 125mm diameter posts** are made of lacquered galvanised steel. The two-tone grey graining finish has a slightly undulating surface for increased scratch resistance. **The caps** are made of rotary moulded polyethylene.



2

2- **The 125mm round posts** are made of laminated timber, which have not been treated with chrome or arsenic. Splinter-free, the laminate provides great strength and dimensional stability. The posts are protected from wear and tear caused by fungi, insects and termites.




3

3- **The coloured panels** are manufactured from 13mm composite compact made up of softwood fibre (70%) and phenolic binder (30%). The material offers excellent resistance in all weather conditions (sun, rain, humidity...). The coloured surfaces are obtained using pigmented resins that provide good levels of resistance to ultraviolet radiation and aggressive cleaning products.




4

4- **The tubes** are made of stainless steel guaranteeing lasting durability and reliability of the equipment. **Injection moulded polyamide fixings** connect the posts to the platforms and the various play features.




5

5- **The 16mm diameter rope** is made of galvanised steel cable covered with polypropylene. **The net fittings** are made of polyamide and used to link three cords together.



6

6- **The salamander climbing holds** are made of injected polyamide, combining rigidity and sturdiness. **The button climbing holds** are made of polypropylene. They are non-toxic, non-flammable and shock and UV resistant.



7

7- **The 420mm diameter tunnel** is made up of a polyethylene.



8

8- **The fixings** are made of stainless steel and protected by anti-vandalism polyamide caps.